

بيانات عن بحث (١) مقدم للترقية

عنوان البحث (باللغة التي نشر بها) :

**Behavior Of Recycled Concrete Beams With Openings In Shear Region:
Experimental And Numerical Study**

مكان النشر (بلغة مكان النشر):

IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE)
e-ISSN: 2278-1684,p-ISSN: 2320-334X, Volume 17, Issue 2 Ser. I (Mar - Apr
2020), PP 01-11

تاريخ الإرسال للنشر : 2020/2 م ، تاريخ القبول للنشر : 2020/3 م ، تاريخ النشر :
2020/3 م

ملخص البحث باللغة الانجليزية

Behavior Of Recycled Concrete Beams With Openings In Shear Region:

Experimental And Numerical Study:The current paper presents an experimental and numerical investigations to study the shear behavior of simply supported natural and recycled coarse aggregate concrete beams. A total of eight beams using two different types of aggregate ‘‘natural and recycled’’ were cast and tested. The beams were divided into two groups, the first group consists of four solid beams, while the second one consists of four beams with openings in the shear zone. Four different replacement ratios of natural coarse aggregates by recycled coarse aggregates: 0% , 25%, 50%, and 100%. Numerical results were compared with the experimental ones to check the validity of the model, a total of 18 numerical models were conducted to study the different parameters that not covered by the experimental program such that, shape of openings, dimension and location of openings along the shear span. The results indicated that compressive, tensile, and flexural strengths decreases as the recycled coarse aggregate increase. The experimental results showed that a reduction in the shear strength of RC beams with openings ranged between 22 % and 30% in comparison to the corresponding control beam without opening.